

STA-STUK - CONTACT ADHESIVE - For bonding acoustic products



Key Benefits

- Ideal for glueing most of our sound absorber products
- Water and heat resistant.
- Adjustable spray nozzle
- Low solvent content
- Heat resistant up to 250°F/121°C

Description

Our Sta-Stuk aerosol contact adhesive is a contact adhesive ideal for bonding our acoustic products to a wide variety of surfaces with no adverse effect. It has a high solids content and is water resistant and heat resistant with permanent flexibility.

Directions

Shake can well before use (especially in cold conditions) Best results are obtained when working in an ambient temperature of 70°F/21°C with surfaces to be bonded properly conditioned. Ensure all surfaces are thoroughly clean and free from moisture, dirt, dust and grease or any other materials that could affect the bond. For vertical or horizontal patterns, adjust the nozzle clockwise to the last of the three marks on the top of the can to obtain the widest spray pattern. Hold can 6 to 8 inches from the surface and apply in even coats, making sure the adhesive 'webs' across the surface. Do not hold closer than 6 inches or 'wet' the surface.



It is important the adhesive 'webs' across the surface and 80-100% coverage is achieved. One surface should be sprayed vertically and the other horizontally. Do not concentrate in one spot or allow the adhesive to 'puddle'. Double coated applications are recommended on porous surfaces (after the first coat has dried, apply a second coat evenly on top). Allow adhesive to tack (approx 2-4 minutes) and bond together with a firm pressure over the entire area. Tack time can vary depending on climate conditions. It is important that maximum uniform pressure is applied to over the entire area bonded to achieve maximum bond strength. Use the Spray Contact Adhesive in well ventilated conditions.

ADDITIONAL INFORMATION AND INSTALLATION DETAIL CAN BE FOUND ON OUR WEBSITE